

Description



PBS

120 mm (H) x 120 mm (W)
x 16 mm (D)



PBR

152 mm (ø) x 16 mm (D)



PBJ

120 mm (H) x 38 mm (W)
x 16 mm (D)



EAS RF Receiver

+ cable 2.50 m



EAS RF Transmitter



EAS RF Key Fob

Large button
and small button

Technical specifications

PUSH PLATE

Type of use	outdoor/indoor
Temperature range	- 20° C to + 55° C
Output contacts	dry output contacts (NO, NC, COM)
Housing	stainless steel
Protection degree	IP52 (housing)

EAS RF

Technology	radio frequency
Transmitter frequency	433.92 MHz
Max. detection distance	25 m
Supply voltage	12 V to 24 V AC ± 15% 12 V to 30 V DC ± 10%
Power consumption	max. 38 mA @ 24 V DC
Standard output	
• contact relay output	COM, NO, NC 42 V AC/DC - 1A 30 W (DC) / 60 VA (AC)
Hold time	0,5 s or 10 s
Length of cable	2.5 m
Max. number of EAS RF Transmitter	10
Manual adjustments	
• 2 dip-switches	output impulse/toggle and hold time (impulse mode)
LED-indicator	
• Receiver	1 yellow LED : record 1 red LED : output
• Key Fob/Transmitter	1 red LED : emission
Battery	
• Key Fob	12 V alkaline type A23
• Transmitter	9 V alkaline

The range



PBS P



PBR P



PBJ P



PBS



PBR



PBJ



PBS H



PBR H



PBJ H

Application



Subject to modification



**For details on our full range of accessories, please contact
Axis Automatic Entrance Systems Limited as below:**

Axis Automatic Entrance Systems Limited
Head Office: Unit 6 Queens Park Industrial Estate,
Studland Road, Northampton NN2 6NA

Tel.: 0844 504 6545 Fax.: 0844 504 6546

Email: sales@axisautomatic.com